



SAFETY DATA SHEET

Revision date 30-Jan-2015

Version 12

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Code ACD498.076

Product Name 12302498 CARBURETOR TUNE-UP COND 6UC

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Washing and cleaning products (including solvent based products)

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation PO Box 1461

Minneapolis, MN 55440

E-mail address msds@valspar.com

Emergency telephone number

United States of America 1-888-345-5732

American Samoa, Guam, Northern Mariana Islands, Puerto Rico, U.S. Virgin Islands Chemtel Number

Section 2: HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation Category 2	
Carcinogenicity	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 2
Gases under pressure	Liquefied gas

Label elements



signal word

DANGER

Hazard Statements

flammable aerosol
Contains gas under pressure; may explode if heated
Causes skin irritation
Causes serious eye irritation
Suspected of causing cancer
May be fatal if swallowed and enters airways

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response

IF exposed or concerned: Get medical advice/attention.

eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Storage

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

Disposal

Dispose of contents/containers in accordance with local regulations.

Hazards not otherwise classified (HNOC)

Propellant is classified as a simple asphyxiant if released in large quantities: May displace oxygen and cause rapid suffocation.

Other hazards

May be harmful if swallowed. Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	10 - 25
Diethylene glycol monobutyl ether	112-34-5	10 - 25
2-Methylnaphthalene	91-57-6	10 - 25
Naphthalene	91-20-3	5 - 10
1-Methylnaphthalene	90-12-0	5 - 10
Distillates, petroleum, hydrotreated heavy naphthenic	64742-52-5	3 - 5

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

IF exposed or concerned: Get medical advice/attention.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Never use pointed jet of water

Specific hazards arising from the chemical

Burning produces heavy smoke. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool closed containers exposed to fire with water. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid breathing vapors or mists. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Remove all sources of ignition.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Product Code ACD498.076
Page 3/10
AGHS - USA OSHA SDS

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Protect from sunlight. Store in a well-ventilated place.

Incompatible materials

Strong oxidizing agents. Acids.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

If this section is blank, no OEL's have been established for the components of this material.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	-	-	-
Diethylene glycol monobutyl ether 112-34-5	TWA: 10 ppm inhalable fraction and vapor	-	-
2-Methylnaphthalene 91-57-6	TWA: 0.5 ppm S*	-	-
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m³ STEL: 15 ppm STEL: 75 mg/m³
1-Methylnaphthalene 90-12-0	TWA: 0.5 ppm S*	-	-
Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5	-	-	-

Legend

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory protection

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

Thermal Protection

No information available

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Aerosol

Appearance No information available

Odor Solvent Color colorless

Odor Threshold No information available

pH value 9

Melting point/freezing pointNo information availableBoiling point / boiling rangeNo information available °C / °F

Boiling point / boiling range
flash point

No information available °C

-91 °C / -132 °F

No information available °C

evaporation rate

Flammability (solid, gas)

No information available
No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor Pressure
vapor density

No information available
No information available
No information available

Density (lbs per US gallon) 7.57 specific gravity .91

Solubility(ies) Not Determined

Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
No information available

Other information

Section 10: STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous polymerizationNone under normal processing.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong oxidizing agents. Acids.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2).

Section 11: TOXICOLOGICAL INFORMATION

Product Information The product has not been tested

Information on likely routes of exposure

Eye contact

Causes serious eye irritation

Skin Contact

Causes skin irritation

Ingestion

May be fatal if swallowed and enters airways

InhalationNot applicable

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 5000 mg/kg(Rat)	> 2 mL/kg(Rabbit)	> 590 mg/m³(Rat) 4 h
Diethylene glycol monobutyl ether 112-34-5	= 3384 mg/kg (Rat)	= 2700 mg/kg (Rabbit)	-
2-Methylnaphthalene 91-57-6	= 1110 mg/kg (Rat)	> 2500 mg/kg (Rat)	-
Naphthalene 91-20-3	= 1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 340 mg/m³ (Rat) 1 h
1-Methylnaphthalene 90-12-0	= 1840 mg/kg (Rat)	-	-
Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5	-	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Numerical measures of toxicity - Product Information

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2972 Mg/kg

Chemical Name	ACGIH	IARC	NTP	OSHA
Solvent naphtha, petroleum,	-	-	-	-
heavy aromatic 64742-94-5				
Diethylene glycol monobutyl ether 112-34-5	-	-	-	-
2-Methylnaphthalene 91-57-6	-	-	-	-
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	Х

1-Methylnaphthalene 90-12-0	-	-	-	-
Distillates, petroleum,	-	-	-	-
hydrotreated heavy				
naphthenic				
64742-52-5				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen.

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans.

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation Causes skin irritation

Serious eye damage/eye irritation Causes serious eye irritation

Skin sensitizationNot applicableRespiratory sensitizationNot applicableGerm cell mutagenicityNot applicable

Carcinogenicity Suspected of causing cancer

Reproductive Toxicity Not applicable Specific target organ toxicity (single Not applicable

exposure)

Specific target organ toxicity

(repeated exposure)

Not applicable

Aspiration hazard May be fatal if swallowed and enters airways

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product has not been tested

Toxic to aquatic life with long lasting effects.

Environmental precautions

Prevent product from entering drains.

Marine pollutant This material meets the definition of a marine pollutant

Persistence and degradability

No information available

Bioaccumulation

No information available

Mobility

No information available

Other adverse effects No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal. Empty

containers must be scrapped or reconditioned.

Section 14: TRANSPORT INFORMATION

<u>DOT</u> <u>IMDG</u> <u>IATA</u>

14.1 UN/ID noORM-DUN1950UN195014.2 Proper shipping nameconsumer commodityAerosolsAerosols

14.3 Hazard Class 2.1 2.1

14.4 Packing Group

14.5 Environmental hazard Yes

Marine pollutant This material meets the definition of a marine pollutant

Marine pollutant Solvent naphtha, petroleum, heavy aromatic, 2-Methylnaphthalene

14.6 Special Provisions

Emergency Response Guide EmS-No Number F-D, S-U

126

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: REGULATORY INFORMATION

International Inventories

DSL - Canadian Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt

from listing

All components are listed or exempt

from listing

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

emical Name SARA 313 - Threshold Values %	
Diethylene glycol monobutyl ether - 112-34-5	1
Naphthalene - 91-20-3	0.1

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes
Sudden release of pressure hazard Yes
Reactive Hazard No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthalene 91-20-3	100 lb	X	X	X

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Naphthalene	100 lb		RQ 100 lb final RQ
91-20-3			RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

WARNING! This product contains a chemical known in the State of California to cause cancer

Chemical Name	California Proposition 65
Naphthalene - 91-20-3	Carcinogen

U.S. EPA Label information

EPA Pesticide registration number Not applicable

U.S. State Right-to-Know Regulations

SAFETY DATA SHEET

Chemical Name].
Solvent naphtha, petroleum, heavy aromatic].
64742-94-5	400.0=
Product Logo ALI	1/14× 11/

Proprietary non-hazardous Ingredient - Proprietary CAS
Diethylene glycol monobutyl ether 112-34-5
2-Methylnaphthalene 91-57-6
Proprietary non-hazardous Ingredient - Proprietary CAS
Naphthalene -
91-20-3
1-Methylnaphthalene
90-12-0
Propane -
74-98-6
Distillates, petroleum, hydrotreated heavy naphthenic
64742-52-5
Butane
106-97-8

Chemical Name
Solvent naphtha, petroleum, heavy aromatic 64742-94-5
Water 7732-18-5
Diethylene glycol monobutyl ether 112-34-5
2-Methylnaphthalene 91-57-6
Oleic acid 112-80-1
Naphthalene 91-20-3
1-Methylnaphthalene 90-12-0
Propane 74-98-6
Distillates, petroleum, hydrotreated heavy naphthenic 64742-52-5
Butane 106-97-8

Section 16: OTHER INFORMATION

HMIS

Health hazards 3* Flammability 4 Physical hazards 0 **Personal Protection** Χ

Supplier Address Valspar Architectural

The Valspar Corporation Headquarters 4999 36th St. 8725 W. Higgins Rd. Suite Grand Rapids, MI 49512 1000 800-253-3957

Chicago, IL 60631 773-628-5500

Product Stewardship Prepared By

Revision date 30-Jan-2015

Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet