

Product identifier used on the label: MAG 1 ATF+4 6/1QT #6062 Stock Number: MG06D4PL Revision Date: 10-27-2017 Replaces:

1. Identification		
Product identifier used on the label:	MAG 1 ATF+4 6/1QT #6062	
Stock Number:	MG06D4PL	
Other means of identification: Synonyms:	No data available	
Recommended use of the chemical and r	restrictions on use:	
Recommended use:	Automatic Transmission Fluid	
Restrictions on use:	Uses other than those described above	
Name, address, and telephone number	Warren Distribution, Inc.	
of the chemical manufacturer,	950 S. 10th St., Suite 300	
importer, or other responsible party:	Omaha, NE 68108-3296	
Phone number:	+01 (800) 825-1235 +01 (402) 341-9397	
E-mail address:	sds@wd-wpp.com	
Emergency phone number:	CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887	

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:	
GHS Classification:	Skin Sensitisation Category 1B
Signal Word:	Warning
Hazard Statements:	May cause an allergic skin reaction
Precautionary Statements:	
Prevention:	Avoid breathing dust/fume/gas/mist/ vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
Response:	If on skin: Wash with plenty of water. Specific treatment (see Sections 4 - 8 of Safety Data Sheet). If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulations.

Product identifier used on the label: MAG 1 ATF+4 6/1QT #6062 Stock Number: MG06D4PL Revision Date: 10-27-2017 Replaces:

Hazards not otherwise classified:

No data available

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS #	%
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	No data available	72623-87-1	90 - 99
Petroleum distillates, hydrotreated light paraffinic	No data available	64742-55-8	1 - 5
Mineral oil	No data available	8012-95-1	1 - 5

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen and get medical attention immediately.
Eye Contact:	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact:	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS.
Most important symptoms/effects, acute and delayed:	May cause an allergic skin reaction
Indication of immediate medical attention and special treatment needed, if necessary:	Specific treatment (see Sections 4 - 8 of Safety Data Sheet).

5. Fire-fighting measures

Product identifier used on the label: MAG 1 ATF+4 6/1QT #6062 Stock Number: MG06D4PL Revision Date: 10-27-2017 Replaces:

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Unsuitable extinguishing media:	No data available
Specific hazards arising from the chemical:	No data available
Hazardous combustion products:	Carbon dioxide, Carbon monoxide
Special protective equipment and precautions for fire-fighters:	No data available

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods and materials for containment and cleaning up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.

7. Handling and storage

Precautions for safe handling:	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Empty containers may retain product residues/ vapors. Use proper bonding and grounding during bulk product transfer. No data available
Conditions for safe storage, including any incompatibilities: Safe storage conditions:	Store in a cool dry place. Isolate from incompatible materials.

Product identifier used on the label: MAG 1 ATF+4 6/1QT #6062 Stock Number: MG06D4PL Revision Date: 10-27-2017 Replaces:

Materials to Avoid/Chemical Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	5 mg/m3	5 mg/m3	10 mg/m3	No data available
Petroleum distillates, hydrotreated light paraffinic	5 mg/m3	5 mg/m3	10 mg/m3	No data available
Mineral oil	5 mg/m3 TWA	5 mg/m3 TWA (excluding metal working fluids, highly & severely refined, inhalable fraction)	No STEL	2500 mg/m3 IDLH

Appropriate engineering controls: Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Facilities storing or using this material should be equipped with an eyewash and safety shower.

Individual protection measures, such as personal protective equipment:		
Respiratory Protection:	Avoid breathing dust/fume/gas/mist/ vapors/spray.	
Respirator Type(s):	None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.	
Eye protection:	Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses. Wear goggles and a Face shield.	
Skin protection:	Wear protective gloves. Inspect gloves for chemical break-through and	

Product identifier used on the label: MAG 1 ATF+4 6/1QT #6062 Stock Number: MG06D4PL Revision Date: 10-27-2017 Replaces:

limits:

limits:

limits: Vapor pressure:

Upper flammability or explosive

Lower flammability or explosive

	replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.
Gloves:	Nitrile, Polyvinyl chloride, Impervious rubber
Other protective equipment:	Wear goggles and a Face shield. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.
General hygiene conditions:	Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

9. Physical and chemical properties	
Appearance (physical state, color etc.):	
Physical state:	Liquid
Color:	Red
Odor:	Mild
Odor Threshold:	Not determined
pH:	No data available
Melting point/freezing point:	
Melting Point:	No data available
Freezing point:	No data available
Initial boiling point and boiling range (°C):	270
Flash Point (°C):	195
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper/lower flammability or explosive	

Not established

Not established

No data available

Product identifier used on the label: MAG 1 ATF+4 6/1QT #6062 Stock Number: MG06D4PL Revision Date: 10-27-2017 Replaces:

Vapor density:	No data available
Relative density:	0.85
Solubility(ies):	Negligible; 0-1%
Partition coefficient: n-octanol/water:	3.9
Auto-ignition temperature:	No data available
Decomposition Temperature:	Not determined
Viscosity:	35.22
Volatile organic compound (VOC)	0.000000
content and percentage of volatiles:	

10. Stability and reactivity

Reactivity:	
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	None expected under standard conditions of storage.
Conditions to avoid (e.g., static discharge, shock, or vibration):	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.
Incompatible materials:	Strong oxidizing agents
Hazardous decomposition products:	No data available

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:					
Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):	Skin contact				
Symptoms related to the physical, chemical and toxicological characteristics:	May cause an allergic skin reaction				
Delayed and immediate effects and also o	hronic effects from short- and long-term exposure:				
Ingestion Toxicity:	Although this product has a low order of acute oral toxicity, aspiration of minute amounts into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.				
Skin Contact:	This material is estimated to be moderately irritating (Primary Irritation Index is 3.0 - 5.0 [rabbits]).Can cause moderate skin irritation, defatting,				

Product identifier used on the label: MAG 1 ATF+4 6/1QT #6062 Stock Number: MG06D4PL Revision Date: 10-27-2017 Replaces:

	and dermatitis. Not likely to cause permanent damage.
Absorption:	Likely to be practically non-toxic based on animal data.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs"). Likely to be practically non-toxic based on animal data.
Eye Contact:	This material is likely to be non-irritating to eyes based on animal data.
Sensitization:	May cause an allergic skin reaction
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Carcinogenicity:	Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
STOT-single exposure:	Based on available data, the classification criteria are not met.
STOT-repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	Based on available data, the classification criteria are not met.
Other information:	No data available

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Mineral oil			Inhalation LC50 (4h) Rat 2062 ppm
Petroleum distillates, hydrotreated light paraffinic	OLD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat = 3900 mg/L
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	OLD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat 2.18 mg/L

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components			
that are known or reported			
to cause cancer.			

12. Ecological information	mation	infor	ogical	Eco	12.
----------------------------	--------	-------	--------	-----	-----

Product identifier used on the label: MAG 1 ATF+4 6/1QT #6062 Stock Number: MG06D4PL **Revision Date: 10-27-2017 Replaces:**

Ecotoxicity (aquatic and terrestrial, where available):

No data available

Ecological Toxicity Data:

Chemical Name	CAS #	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	> 1000 mg/L	No data available	Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	72623-87-1	> 1000 mg/L	No data available	Aquatic LC50 (96h) > 5000 mg/L

Persistence and degradability: No data available

Bioconcentration is not expected to occur.

This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.

No data available Other adverse effects (such as

hazardous to the ozone layer):

Bioaccumulative potential:

Mobility in soil:

13. Disposal considerations	
Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:	Dispose of contents and container in accordance with local/regional/national/international regulations.
Contaminated packaging:	Containers of this material may be hazardous when emptied. Recycle containers whenever possible.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

DOT Basic Description:

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).

International carriage of dangerous goods by sea (IMDG/IMO):

Product identifier used on the label: MAG 1 ATF+4 6/1QT #6062 Stock Number: MG06D4PL Revision Date: 10-27-2017 Replaces:

UN number:	Not regulated by IMDG
UN Proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group, if applicable:	Not applicable
International carriage of dangerous good	s by air (IATA):
UN number:	Not regulated by IATA
UN Proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group, if applicable:	Not applicable
Environmental hazards (e.g., Marine pollutant (Yes/No)):	None.
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	No data available
Special precautions which a user needs to be aware of or needs to comply with	No data available

to be aware of or needs to comply with in connection with transport or conveyance either within or outside their premises:

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status:

All components of this material are on the US TSCA Inventory or are exempt.

Regulated Components:

Chemical Name	CAS #	CERCLA	Sara EHS	Sara 313	U.S. HAP
Lubricating oils					
(petroleum), C20-50,	72623-87-1	Ν	N	N	N
hydrotreated neutral	/2025-0/-1	IN	IN	IN	IN
oil-based					
Petroleum distillates,					
hydrotreated light	64742-55-8	Ν	Ν	Ν	N
paraffinic					
Mineral oil	8012-95-1	Ν	N	N	N
1-Decene,	68037-01-4	Ν	Ν	N	N

Product identifier used on the label: MAG 1 ATF+4 6/1QT #6062 Stock Number: MG06D4PL Revision Date: 10-27-2017 Replaces:

homopolymer,			
hydrogenated			

Chemical Name	CAS #	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	Ν	Ν	Ν	Ν
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	Ν	Ν	Ν	Ν
Mineral oil	8012-95-1	Ν	N	Ν	N
1-Decene, homopolymer, hydrogenated	68037-01-4	Ν	Ν	Ν	N

Chemical Name	CAS #	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Lubricating oils						
(petroleum), C20-50,	72623-87-1	Ν	Ν	Ν	N	Ν
hydrotreated neutral						
oil-based						
Petroleum distillates,						
hydrotreated light	64742-55-8	Y	N	N	N	N
paraffinic						
Mineral oil	8012-95-1	Y	Y	Y	N	Y
1-Decene,						
homopolymer,	68037-01-4	Ν	N	N	N	N
hydrogenated						

16. Other information, including date of preparation or last revision.

SDS Prepared by:

CHOLMES 10-27-2017

Revision Date:

Product identifier used on the label: MAG 1 ATF+4 6/1QT #6062 Stock Number: MG06D4PL Revision Date: 10-27-2017 Replaces:

Revision Number:

Reason for revision: References: Other Info:

Disclaimer:

32

NEW VERSION No data available No data available

This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.